

**Bobcat®***One Tough Animal.*

360–585 CFM AIR COMPRESSORS

PA400P, PA435, PA450, PA600

⌚ MEA & CIS



POWER THROUGH DEMANDING TASKS WITH OUR 360–585 CFM AIR COMPRESSORS

Engineered for excellence, our single-axle medium compressors deliver up to 585 CFM (16.6 m³/min) at 150 PSI, or up to 200 PSI for the high-pressure PA400P model. Features like the fuel gauge, emergency stop, and battery disconnecter come standard. Plus, with a focus on environmental protection, the bottom sheet prevents dust contamination, while acoustic foam minimizes noise emissions.

At Bobcat, we understand the importance of having the right products and services. For more information, contact your local dealer or visit: www.bobcat.com.



KEY FEATURES

SPECIFICATIONS				
	PA400P	PA435	PA450	PA600
GENERAL				
Emission compliance	non emission			
Free air delivery	10.2 m³/min (360 CFM)	11.3 m³/min (400 CFM)	12.8 m³/min (450 CFM)	16.6 m³/min (585 CFM)
Rated operating pressure	12 bar (175 PSI)	10.3 bar (150 PSI)		6.9 bar (100 PSI)
Rated operating pressure – high pressure mode	13.8 bar (200 PSI)	–		
ENGINE				
Make	Cummins			
Model	6BTA5.9C	6BT5.9C	6BTA5.9C	6BTA5.9C
Number of cylinders	6			
Full load speed	2 300 RPM	2 550 RPM	2 300 RPM	
Power	123 kW	107 kW	123 kW	126 kW
Electrical	24 V	12 V	24 V	
Cooling	liquid			
Fuel tank capacity	200 l			
WEIGHTS				
Weight (net) fixed / adjustable	2 065 kg			
Weight (working) fixed / adjustable	2 300 kg			
Weight on shipping support (net)	1 980 kg			

STANDARD FEATURES				
Central lifting point	✓	✓	✓	✓
Fuel/water separator	✓	✓	✓	✓
High ambient	✓	✓	✓	✓
Standard non-metallic fan	✓	✓	✓	✓
Battery isolator	✓	✓	✓	✓
Emergency stop	✓	✓	✓	✓
Fixed height unbraked r/gear 3" in eye	–	✓	✓	✓
Fuel gauge	✓	✓	✓	✓

